

INSTALL INFORMATION

Standard Installation:

Mount dish on an outside wall of the dwelling with appropriate hardware, within 125 feet cable length of TV.

Route all cables to the TV either through an exterior wall (frame or one layer of masonry) or from a basement.

Connect the receiver to an existing telephone jack within 25' of TV (if available) in the same room with the supplied telephone wire.

Connect existing equipment that was connected to the TV prior to the install of the new receiver(s)

Multi Switch up to a 6 x 8 if needed

1 Short Stay for KA/KU dish is included

Professional Installation:

If you request or require anything above and beyond standard professional installation, you will pay the installer for those additional services at the time of the installation.

You and your installer should discuss any additional service requirements and costs prior to the start of the installation. Additional services for which you will pay the installer directly may include:

SECOND RECEIVER INSTALLATION

SECOND TELEVISION HOOK-UP

STEREO SYSTEM HOOK- UP (NOT PREVIOUSLY HOOKED UP)

CHIMNEY MOUNT

ADDITIONAL COAX CABLE RUN

ADDITIONAL RECEIVERS

EXTENSIVE WIRING

SPECIAL HARDWARE OR ACCESSORIES

WALL FISHING OF COAX CABLE

REPLACING EXSISTING CABLE NOT COMPATIBALE (Includes anything other than RG6 3 GHZ or CAT5)

POLE MOUNT REMOVAL DIG/CUT

POLE MOUNT/ PER CUSTOMERS REQUEST

SIDEWALK BORE

MIRROR OUTLET

ADDITIONAL OUTLETS WITHOUT RECEIVERS

ADDITIONAL OUTLETS WITH RECEIVERS

SEPARATE TRIP ADDITIONAL OUTLETS

NON -PENETRATING/ SLED MOUNT

BALCONY MOUNT/BRACKETS

FLAT CABLE JUMPER

BURY CABLE/ OUTLET

LINE AMPS

DIPLEXERS (2)

WIRELESS PHONE JACK

RELOCATE DISH

6 X 16 MULTI SWITCH INSTALLATIONS

SPLITTERS TO OPERATE MORE THAN 1 TV WITH 1 RECEIVER

THIS LIST IS NOT ALL INCLUSIVE

CUSTOMER SIGNATURE: _____ **DATE:** _____